

# ISUZU

Vehicle Make	Year Range	Manufacturer of Axle	Axle Model	Spline Count	Cover Bolts	Special Notes	Lock-Right
							Open
<b>Amigo</b>							
	Rear Axle						
	1998 - 2000	GM	7.625" rg	28	10	2WD	1931
	1998 - 2000	DANA	Model 44	30	10	4WD	2410
<b>Hombre</b>							
	Front Axle (see notice at bottom of page)						
	1996 - 1999	GM	7.2" rg	26			1935
	Rear Axle						
	1996 - 1999	GM	7.625" rg	28	10	2WD	1931
<b>P'up</b>							
	Rear Axle						
	1990 - 1994	GM	7.5" rg	26	10	2WD U.S. Built	1930
<b>Rodeo</b>							
	Front Axle (see notice at bottom of page)						
	1998 - 2000	DANA	Model 44	30	10	IFS	2410
	Rear Axle						
	1993 - 2000	DANA	Model 44	30	10		2410
	1991 - 1992	ISUZU		26		4WD (Japan)	
	1991 - 2000	GM	7.625" rg	28	10	4cyl & 2WD	1931
<b>Trooper</b>							
	Rear Axle						
	1984 - 1987	ISUZU		17			3111
	1988 - 1991	ISUZU		26			

## NOTICE REGARDING ACCURACY OF THIS GUIDE:

Powertrax has attempted to make this Application Guide as accurate as possible. However, Powertrax cannot guarantee correctness. Identical model vehicles may have different axles or differentials than stated in this guide depending on original options ordered and other factors. It is advisable to check the vehicle to determine precisely which differential and axle are present. **IF YOU HAVE ANY QUESTIONS, PLEASE DON'T HESITATE TO CONTACT US AT 800-578-1020.**

## NOTICE REGARDING FRONT AXLE APPLICATIONS:

The Powertrax Lock-Right Locker works well on the front axle of 4-wheel drive vehicles provided a couple of important guidelines are followed. The Lock-Right Locker should be used only on vehicles equipped with locking hubs on the front axle or with front axle disconnect. In addition, the vehicle must not be equipped with full time 4-wheel drive. Vehicles equipped with a Lock-Right Locker on the front axle should not be operated on the highway with the front hubs locked and 4-wheel drive engaged. Following these guidelines will ensure very on-road driveability while still providing maximum off-road traction.